TEMPT 3



SPECIFIKACIJE

OKVIR	
VELIKOSTI	27.5": XS, S 29": S, M, L
BARVE	Morning Haze, Airglow
OKVIR	ALUXX-grade aluminum, disc
VILICE	SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
KOMPONENTE	
KRMILO	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
GRIPS	Giant Sole-O
OPORA KRMILA	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50mm
OPORA SEDEŽA	Giant Sport, 30.9mm 27.5" XS:100x350mm, S: 100x350mm 29" S: 100x375mm, M:100x375mm, L: 100x375mm
SEDEŽ	Contact Ergo
PEDALA	MTB caged
POGON	
PRESTAVNE ROČICE	Shimano, Acera 2x8, SL-M315-2L, SL-M315-8R
PREDNJI MENJALNIK	Shimano, Acera, FD-M315-TS
ZADNJI MENJALNIK	Shimano, Acera 2x8, RD M3020-8
ZAVORE	Tektro, hydraulic, Tektro rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Tektro
VERIŽNIK	Shimano, Acera, CS-HG31-8, 11-34
VERIGA	KMC 8.3
GONILKE Z VERIŽNIKI	Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	cartridge

OBROČNIKI	
OBROČI	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
PESTA	[F] QR alloy, sealed bearing, [R] Giant Tracker hub, 12x142 thru axle, 24-pawl drive
NAPERE	stainless, 14g
PLAŠČI	Maxxis Ikon 27.5x2.2 or Maxxis Ikon 29x2.2, wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32t

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Dolžina sedežne cevi (mm)	330	365	380	410	440
Seat Post Insertion Depth (mm)	280	310	330	360	220
Kot sedežne cevi	74,0°	74,0°	74,5°	74,5°	74,5°
Top Tube Length (mm)	538	558	571	599	629
Višina glave okvirja (mm)	90	95	90	100	120
Krmilni kot	67,0°	67,0°	67,5°	67,5°	67,5°
Zamik vpetja osi (mm)	44	44	44	44	44
Trail (mm)	105,2	105,2	108,9	108,9	108,9
Medosna razdalja (mm)	1080	1101	1129	1158	1190
Dolžina cevi ob verigi (mm)	440	440	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55
Oddaljenost zgornje cevi od gonilne osi (mm)	548	553	593	602	620
Doseg (mm)	381	400	407	432	457
Višina zgornje cevi (mm)	680	689	689	708	
Širina krmila (mm)	690	690	690	690	760
Dolžina opore krmila (mm)	40	40	40	50	60
Dolžina gonilke (mm)	165	165	170	170	170

Vse navedene specifikacije se lahko spremenijo brez obvestila.