



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
MANDO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PANTALLA	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERÍA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARGADOR	Giant EnergyPak smart charger 4A
CONECTIVIDAD	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	XS, S, M, L (XS-S: 27.5, M-L: 29er)
COLORES	Lunar Eclipse
CUADRO	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
HORQUILLA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIGUADOR	n/a
COMPONENTES	
MANILLAR	Giant Connect TR Riser 31.8x690-750mm
PUÑOS	Giant Sole-O Grip
POTENCIA	Giant Contact
TIJA DE SILLÍN	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SILLÍN	Liv Ergo Trail ESG
PEDALES	Anti-slip Platform
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues
CAMBIO TRASERO	Shimano Cues 9-speed
FRENOS	Shimano MT200, hydraulic disc, 180mm [F/R]
PALANCAS DE FRENOS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
CADENA	KMC eGlide NP/BK, e-bike optimized
JGO. PLATOS Y BIELAS	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms, (XS-S: 160mm, M-L: 165mm)
CAJA DE PEDALIER	-

RUEDAS	
LLANTAS	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
BUJES	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
RADIOS	Stainless steel
CUBIERTAS	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESORIOS	
LUCES	-
PORTA-EQUIPAJES	-

Precio: 2.599,00 €

GEOMETRÍA

CUADRO	XS	S	M
Longitud del tubo del sillín (mm)	365	405	445
Seat Post Insertion Depth (mm)	170	200	240
Ángulo del tubo del sillín	78,0°	78,0°	74,0°
Longitud del tubo superior (mm) (mm)	560	570	595
Longitud del tubo de dirección (mm) (mm)	110	115	105
Ángulo del tubo de dirección	68,0°	68,0°	68,0°
Inclinación de la horquilla (mm)	44	44	46
Trail (mm) (mm)	106	106	104,5
Distancia entre ejes (mm) (mm)	1151	1162	1139
Longitud de la vaina (mm) (mm)	450	450	470
Caída del eje de pedalier (mm) (mm)	45	45	60
Stack (mm) (mm)	596	600	618
Reach (mm) (mm)	433	442	417
Altura del suelo al tubo (mm) (mm)	717	732	750
Ancho del manillar (mm) (mm)	690	750	750
Longitud de la potencia (mm) (mm)	50	50	50
Longitud de las bielas (mm) (mm)	165	165	165
Tamaño de ruedas	27.5+	27.5+	29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.