TEMPT E+



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERÍA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONECTIVIDAD	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	XS, S, M, L (XS-S: 27.5, M-L: 29er)
COLORES	Lunar Eclipse, Seafoam Green
CUADRO	ALUXX aluminum, Overdrive 1½ - 1⅛" head tube, integrated KSA40 kickstand mount
TIJERA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIGUADOR	n/a
COMPONENTES	
MANUBRIO	Giant Connect TR Riser 31.8x690~750mm
GRIPS	Giant Sole-O Grip
POTENCIA	Giant Contact
POSTE DE ASIENTO	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ASIENTO	Liv Ergo Trail ESG
PEDALES	Anti-slip Platform
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues
CAMBIO TRASERO	Shimano Cues 9-speed
FRENOS	Shimano MT200, hydraulic disc, 180mm [F/R]
PALANCAS DE FRENOS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
CADENA	KMC eGlide NP/BK, e-bike optimized
MULTIPLICACIÓN	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms, (XS-S: 160mm, M-L: 165mm)
EJE DE CENTRO	-

RUEDAS	
RUEDAS	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
MAZAS	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
RAYOS	Stainless steel
NEUMÁTICOS	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESORIOS	
LUCES	-
CARRIER	-

GEOMETRÍA

CUADRO	XS	S	M	L
Longitud de la Base del Poste de Asiento (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Ángulo de la Base del Poste de Asiento	78.0°	78.0°	74.0°	74.0°
Longitud del Tubo Superior (mm)	560	570	595	615
Longitud del Telescopio (mm)	110	115	105	115
Ángulo del Telescopio	68.0°	68.0°	68.0°	68.0°
Rake (mm)	44	44	46	46
Trail (mm)	106	106	104.5	104.5
Distancia entre Ejes (mm)	1151	1162	1139	1160
Longitud de Vaina Inferior (mm)	450	450	470	470
Caída del Eje de Centro (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Altura del Tubo Superior al Suelo (mm)	717	732	750	765
Ancho del Manubrio (mm)	690	750	750	750
Longitud de la Potencia (mm)	50	50	50	60
Longitud de la Biela (mm)	165	165	165	
Tamaño de las Ruedas	27.5+	27.5+	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.