

TEMPT E+ EX



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	XS, S, M, L (XS-S: 27.5, M-L: 29er)
COLORS	Sandshell
FRAME	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
FORK	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
SHOCK	n/a
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x690~750mm
GRIPS	Giant Sole-O Grip
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Ergo Trail ESG
PEDALS	Anti-slip Platform
DRIVETRAIN	
SHIFTERS	Shimano Cues
REAR DERAILLEUR	Shimano Cues 9-speed
BRAKES	Shimano MT200, hydraulic disc, 180mm [F/R]
BRAKE LEVERS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
CHAIN	KMC eGlide NP/BK, e-bike optimized
CRANKSET	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arm, (XS-S: 160mm, M-L: 165mm)
BOTTOM BRACKET	-

WHEELS	
RIMS	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
HUBS	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
SPOKES	Stainless steel
TIRES	Maxxis Rekon XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESSORIES	
LIGHTING	Recon EL50 Axa BlueLine Steady E6 rear
CARRIER	Rack-It MIK

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Seat Tube Angle	78,0°	78,0°	74,0°	74,0°
Top Tube Length (mm)	560	570	595	615
Head Tube Length (mm)	110	115	105	115
Head Tube Angle	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	44	44	46	46
Trail (mm)	106	106	104,5	104,5
Wheelbase (mm)	1151	1162	1139	1160
Chain Stay Length (mm)	450	450	470	470
Bottom Bracket Drop (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Stand Over Height (mm)	717	732	750	765
Handlebar Width (mm)	690	750	750	750
Stem Length (mm)	50	50	50	60
Crank Length (mm)	165	165	165	
Wheel Size	27.5+	27.5+	29"	29"

All specifications listed are subject to change without notice.