

TEMPT E+ EX



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERI	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
FORBINDELSE	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSER	XS, S, M, L (XS-S: 27.5, M-L: 29er)
FARVER	Sandshell
RAMME	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
FORGAFFEL	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
BAGDÆMPER	n/a
KOMPONENTER	
STYR	Giant Connect TR Riser 31.8x690-750mm
GREB / STYRBÅND	Giant Sole-O Grip
FREMPIND	Giant Contact
SADELPIND	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Liv Ergo Trail ESG
PEDALER	Anti-slip Platform
GEARGRUPPE	
SKIFTEGREB	Shimano Cues
BAGSKIFTER	Shimano Cues 9-speed
BREMSE	Shimano MT200, hydraulic disc, 180mm [F/R]
BREMSEGREB	Shimano MT-200
KASSETTE	Shimano Cues, 11-41T, 9-speed
KÆDE	KMC eGlide NP/BK, e-bike optimized
KRANKSÆT	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arm, (XS-S: 160mm, M-L: 165mm)
KRANKBOKS	-

HJUL	
FÆLGE	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
NAV	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
EGER	Stainless steel
DÆK	Maxxis Rekon XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
TILBEHØR	
LYGTER	Recon EL50 Axa BlueLine Steady E6 rear
BAGGEBÆRER	Rack-It MIK

Pris: 23.699,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørlængde (mm)	365	405	445	485
Sadelpindindsætningsdybde (mm)	170	200	240	260
Sadelrørvinkel	78,0°	78,0°	74,0°	74,0°
Overrørlængde (mm)	560	570	595	615
Kronrørlængde (mm)	110	115	105	115
Kronrørvinkel	68,0°	68,0°	68,0°	68,0°
Forgaffel fremspring (rake) (mm)	44	44	46	46
Sti (mm)	106	106	104,5	104,5
Akselafstand (mm)	1151	1162	1139	1160
Kædestagslængde (mm)	450	450	470	470
Krankboks drop (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Skridthøjde (mm)	717	732	750	765
Styrbredde (mm)	690	750	750	750
Frempindslængde (mm)	50	50	50	60
Pedalarmslængde (mm)	165	165	165	
Hjulstørrelse	27.5+	27.5+	29"	29"

Alle de anførte specifikationer kan ændres uden varsel.