TEMPT E+ EX





SPECS

HYBRID CYCLING TECHNOLO	OGY
MOTOR	SyncDrive Sport 2, 75Nm, Powered by Yamaha
CONTROLLER	RideControl Dash 2, full colour LCD screen
DISPLAY	RideControl Dash 2, full colour LCD screen
BATTERY	EnergyPak 430Wh, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	27.5" XS, S 29": M, L
COLOURS	Sandshell
FRAME	ALUXX-Grade aluminium, disc
FORK	SR Suntour XCM 32 DS Coil, Boost, 100mm travel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser, 31.8mm
GRIPS	Giant Sole-O Grip
STEM	Giant Contact, alloy, 8-degree 50mm
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv ErgoContact Trail
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Cues
REAR DERAILLEUR	Shimano Cues 9-speed
BRAKES	Shimano MT200, hydraulic disc, 180mm [F/R]
BRAKE LEVERS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
CHAIN	KMC eGlide, e-bike optimised
CRANKSET	Forged alloy, 36T, (XS/S) 160mm, (M/L) 165mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant alloy 27.5" or 29"
HUBS	Giant eTracker Boost alloy 6-bolt disc, 28H
SPOKES	Stainless steel
TIRES	Maxxis Rekon 27.5x2.4" or 29x2.4"
EXTRAS	Aluminium fenders, KSA40 direct mount kickstand
ACCESSORIES	
LIGHTING	Giant Recon E HL50, Axa BlueLine Steady E6 rear
CARRIER	Giant Rack-lt MIK

Price: \$4,799.00

GEOMETRY

Top Tube Length (mm) 560 570 595 63 Head Tube Length (mm) 110 115 105 11 Head Tube Angle 68.0° 68.0° 68.0° 68 Fork Rake (mm) 44 44 46 46	0 .0° 5
Seat Tube Angle 78.0° 78.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0° 74.0°	.0° 5
Top Tube Length (mm) 560 570 595 67 Head Tube Length (mm) 110 115 105 17 Head Tube Angle 68.0° 68.0° 68.0° 68 Fork Rake (mm) 44 44 46 46 Wheelbase (mm) 1151 1162 1139 11 Chain Stay Length (mm) 450 450 470 47	5
Head Tube Length (mm) 110 115 105 11 Head Tube Angle 68.0° 68.0° 68.0° 68 Fork Rake (mm) 44 44 46 46 Wheelbase (mm) 1151 1162 1139 11 Chain Stay Length (mm) 450 450 470 47	5
Head Tube Angle 68.0° 68.0° 68.0° 68 Fork Rake (mm) 44 44 46 46 Wheelbase (mm) 1151 1162 1139 11 Chain Stay Length (mm) 450 450 470 47	
Fork Rake (mm) 44 44 46 46 Wheelbase (mm) 1151 1162 1139 11 Chain Stay Length (mm) 450 450 470 47	.0°
Wheelbase (mm) 1151 1162 1139 11 Chain Stay Length (mm) 450 450 470 47	-
Chain Stay Length (mm) 450 450 470 47	
	60
Bottom Bracket Drop (mm) 45 45 60 60	0
Stack (mm) 596 600 618 62	7
Reach (mm) 433 442 417 45	5
Stem Length (mm) 50 50 50 60	
Wheel Size 27.5+ 27.5+ 29" 29	

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.