

TEMPT E+ EX



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZ	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	XS, S, M, L (XS-S: 27.5, M-L: 29er)
BOJE	Sandshell
OKVIR	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
VILICA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8x690-750mm
GRIPS	Giant Sole-O Grip
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Liv Ergo Trail ESG
PEDALE	Anti-slip Platform
POGON	
RUČICE MJENJAČA	Shimano Cues
STRAŽNJI MJENJAČ	Shimano Cues 9-speed
KOČNICE	Shimano MT200, hydraulic disc, 180mm [F/R]
RUČICE KOČNICA	Shimano MT-200
KAZETA	Shimano Cues, 11-41T, 9-speed
LANAC	KMC eGlide NP/BK, e-bike optimized
POGON	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arm, (XS-S: 160mm, M-L: 165mm)
OSOVINA POGONA (BB)	-

KOTAČI	
OBRUČI	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
NABE	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
ŽBICE	Stainless steel
GUME	Maxxis Rekon XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
DODACI	
SVJETLA	Recon EL50 Axa BlueLine Steady E6 rear
NOSAČ	Rack-It MIK

GEOMETRIJA

OKVIR	XS	S	M	L
Dužina cijevi sjedala (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Kut cijevi sjedala	78,0°	78,0°	74,0°	74,0°
Dužina gornje cijevi (mm)	560	570	595	615
Dužina prednje cijevi (mm)	110	115	105	115
Kut vilice	68,0°	68,0°	68,0°	68,0°
Zakrivljenost vilice (offset) (mm)	44	44	46	46
Staza (mm)	106	106	104,5	104,5
Međuosovinski razmak kotača (mm)	1151	1162	1139	1160
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	450	450	470	470
Položaj osovine pogona (mm)	45	45	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	596	600	618	627
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	433	442	417	435
Prekoračna visina (mm)	717	732	750	765
Širina volana (mm)	690	750	750	750
Dužina lule volana (mm)	50	50	50	60
Dužina poluge pedale (mm)	165	165	165	
Veličina kotača	27.5+	27.5+	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.