



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
TIPALO	RideControl Dash
PRIKAZOVALNIK	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
OKVIR	
VELIKOSTI	XS, S, M, L, (XS-S: 27.5, M-L: 29er)
BARVE	carry-over
OKVIR	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA18 kickstand mount
VILICE	SR Suntour XCM 32 ATB Coil, NLO, 29"/27.5", 100mm travel, Tapered 1½ - 1⅝" steerer (XS-S: 27.5", M-L: 29")
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Liv Sport
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Altus
PREDNJI MENJALNIK	n/a
ZADNJI MENJALNIK	Shimano Alivio M3100, 9-speed
ZAVORE	Tektro HD-M286, hydraulic disc, 180mm[F], 160mm[R]
ZAVORNE ROČICE	Tektro HD-M286
VERIŽNIK	Shimano CS-HG200, 11-36T
VERIGA	KMC e.9 Sport, e-bike optimized
GONILKE Z VERIŽNIKI	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	Liv, GX03V, 27.5 / 29er, Alluminum(XS-S: 27.5, M-L: 29er)
PESTA	Giant eTracker Sport, [F] 9mm QR [R] 135mm QR
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon Race 27.5 x 2.25" / 29 x 2.25", Wire Bead, Dual Compound 60TPI(XS-S: 27.5, M-L: 29er)
DODATNA OPREMA	
SVETILA	Herrmans H-BLACK MR4Axa BlueLine Steady E6 rear
PRTLJAŽNIK	Rack-It MIK

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	365	405	445	485
Kot sedežne cevi	74,0°	73,5°	73,0°	73,0°
Top Tube Length (mm)	545	570	595	615
Višina glave okvirja (mm)	105	115	105	115
Krmilni kot	68,0°	68,0°	68,0°	68,0°
Zamik vpetja osi (mm)	42	42	46	46
Trail (mm)	104	104	99	99
Medosna razdalja (mm)	1112	1132	1159	1179
Dolžina cevi ob verigi (mm)	475	475	475	475
Bottom Bracket Drop (mm)	50	50	45	45
Oddaljenost zgornje cevi od gonilne osi (mm)	591	600	603	612
Doseg (mm)	376	392	411	428
Višina zgornje cevi (mm)	693	722	761	768
Širina krmila (mm)	690	690	750	750
Dolžina opore krmila (mm)	40	40	50	60
Dolžina gonilke (mm)	165	165	170	170
Velikost obročnikov	27.5"	27.5"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.