



## TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
<b>MOOTTORI</b>	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
<b>OHJAUSYSIKÖ</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
<b>NÄYTTÖ</b>	Giant RideControl Dash 2, high-angle visibility, full color LCD display
<b>AKKU</b>	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>LATURI</b>	Giant EnergyPak smart charger 4A
<b>YHTEYDET MUIHIN LAITTEISIIN</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RUNKO	
<b>KOOT</b>	XS, S, M, L (XS-S: 27.5, M-L: 29er)
<b>VÄRIT</b>	Lunar Eclipse, Seafoam Green
<b>RUNKO</b>	ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount
<b>HAARUKKA</b>	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
<b>ISKUNVAIMENNIN</b>	n/a
KOMONENTIT	
<b>OHJAUSTANKO</b>	Giant Connect TR Riser 31.8x690-750mm
<b>GRIPIT</b>	Giant Sole-O Grip
<b>OHJAINKANNATIN</b>	Giant Contact
<b>SATULATOLPPA</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SATULA</b>	Liv Ergo Trail ESG
<b>POLKIMET</b>	Anti-slip Platform
VOIMANSIIRTO	
<b>VAIHDEVIPI</b>	Shimano Cues
<b>TAKAVAIHTAJA</b>	Shimano Cues 9-speed
<b>JARRUT</b>	Shimano MT200, hydraulic disc, 180mm [F/R]
<b>JARRUKAHVAT</b>	Shimano MT-200
<b>RATASPAKKA</b>	Shimano Cues, 11-41T, 9-speed
<b>KETJUT</b>	KMC eGlide NP/BK, e-bike optimized
<b>KAMPISARJA</b>	Forged aluminum direct-mount chainring steel 36T, Forged aluminum crank arms, (XS-S: 160mm, M-L: 165mm)
<b>KESKIÖ</b>	-

RENKAAT	
<b>VANTEET</b>	Liv, GX03V, 27.5 / 29, Alluminium (XS-S: 27.5, M-L: 29)
<b>NAVAT</b>	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>PINNAT</b>	Stainless steel
<b>RENKAAT</b>	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
TARVIKKEET	
<b>VALOT</b>	-
<b>TAVARATLINE</b>	-

Suositushinta: 2 999,00 €

## GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	365	405	445	485
Satulatolpan asennussyvyys (mm)	170	200	240	260
Satulaputken kulma	78,0°	78,0°	74,0°	74,0°
Vaakaputken pituus (mm)	560	570	595	615
Emäputken pituus (mm)	110	115	105	115
Emäputken kulma	68,0°	68,0°	68,0°	68,0°
Haarukan offset (mm)	44	44	46	46
Trail-mitta (mm)	106	106	104,5	104,5
Akseliväli (mm)	1151	1162	1139	1160
Takahaarukan alaputken pituus (mm)	450	450	470	470
Keskiön pudotus (mm)	45	45	60	60
Stack-mitta (mm)	596	600	618	627
Reach-mitta (mm)	433	442	417	435
Standover-mitta (mm)	717	732	750	765
Ohjaustangon leveys (mm)	690	750	750	750
Ohjainkannattimen pituus (mm)	50	50	50	60
Kammen pituus (mm)	165	165	165	
Rengaskoko	27.5+	27.5+	29"	29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.