

TEMPT E+



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
COMANDO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERIA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARICATORE	Giant EnergyPak smart charger 4A
CONNETTIVITÀ	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	XS, S, M, L (XS-S: 27.5, M-L: 29er)
COLORAZIONI	Seafoam Green
TELAIO	ALUXX aluminum, Overdrive 1½ - 1⅞" head tube, integrated KSA40 kickstand mount
FORCELLA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMMORTIZZATORE	n/a
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser 31.8x690-750mm
MANOPOLE	Giant Sole-O Grip
ATTACCO MANUBRIO	Giant Contact
REGGISSELLA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLA	Liv Ergo Trail ESG
PEDALI	Anti-slip Platform
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Cues
DERAGLIATORE POSTERIORE	Shimano Cues 9-speed
FRENI	Shimano MT200, hydraulic disc, 180mm [F/R]
COMANDI FRENO	Shimano MT-200
PACCO PIGNONI	Shimano Cues, 11-41T, 9-speed
CATENA	KMC eGlide NP/BK, e-bike optimized
GUARNITURA	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms, (XS-S: 160mm, M-L: 165mm)
MOVIMENTO CENTRALE	-

RUOTE	
CERCHI	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
MOZZI	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
RAGGI	Stainless steel
COPERTONI	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESSORI	
ILLUMINAZIONE	-
PORTAPACCHI	-

Prezzo: 2.699,00 €

GEOMETRIA

TELAIO	XS	S	M	L
Lunghezza Tubo Sella (mm)	365	405	445	485
Profondità inserimento reggisella (mm)	170	200	240	260
Angolo Tubo Sella	78,0°	78,0°	74,0°	74,0°
Lunghezza Tubo Orizzontale (mm)	560	570	595	615
Lunghezza Tubo Sterzo (mm)	110	115	105	115
Angolo Sterzo	68,0°	68,0°	68,0°	68,0°
Rake Forcella (mm)	44	44	46	46
Avancorsa (mm)	106	106	104,5	104,5
Interasse (mm)	1151	1162	1139	1160
Lunghezza Carro Posteriore (mm)	450	450	470	470
Drop Movimento Centrale (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Altezza stand over (mm)	717	732	750	765
Larghezza Manubrio c/c (mm)	690	750	750	750
Lunghezza Attacco Manubrio (mm)	50	50	50	60
Lunghezza Pedivella (mm)	165	165	165	
Dimensione Ruote	27.5+	27.5+	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.