



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
ACCU	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	XS, S, M, L (XS-S: 27.5, M-L: 29er)
KLEUREN	Lunar Eclipse
FRAME	ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Connect TR Riser 31.8x690-750mm
HANDVATTEN	Giant Sole-O Grip
STUURPEN	Giant Contact
ZADEL	Liv Ergo Trail ESG
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Shimano Cues
ACHTERDERAILLEUR	Shimano Cues 9-speed
REMMEN	Shimano MT200, hydraulic disc, 180mm [F/R]
REMHENDELS	Shimano MT-200
CASSETTE	Shimano Cues, 11-41T, 9-speed
AANDRIJVING	KMC eGlide NP/BK, e-bike optimized
CRANKSET	Forged aluminum direct-mount chainring steel 36T, Forged aluminum crank arms, (XS-S: 160mm, M-L: 165mm)
BOTTOM BRACKET	-

WIELSET	
VELGEN	Liv, GX03V, 27.5 / 29, Aluminum (XS-S: 27.5, M-L: 29)
NAVEN	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless steel
BANDEN	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESSOIRES	
VERLICHTING	-
DRAGER	-

Adviesprijs: € 2.799,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Zitbuis hoek	78,0°	78,0°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	560	570	595	615
Balhoofdbuis Lengte (mm)	110	115	105	115
Balhoofdbuis Hoek	68,0°	68,0°	68,0°	68,0°
Vork Sprong (mm)	44	44	46	46
Naloop (mm)	106	106	104,5	104,5
Wielbasis (mm)	1151	1162	1139	1160
Liggende achtervork lengte (mm)	450	450	470	470
Bottom Bracket Drop (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Stand Over Height (mm)	717	732	750	765
Stuur breedte (mm)	690	750	750	750
Stuurpen Lengte (mm)	50	50	50	60
Cranklengte (mm)	165	165	165	
Wielmaat	27.5+	27.5+	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.