

# TEMPT E+



## SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
<b>MOTOR</b>	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
<b>SENSOR</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
<b>ECRÃ</b>	Giant RideControl Dash 2, high-angle visibility, full color LCD display
<b>BATERIA</b>	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CARREGADOR</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
QUADRO	
<b>TAMANHOS</b>	XS, S, M, L (XS-S: 27.5, M-L: 29er)
<b>CORES</b>	Lunar Eclipse
<b>QUADRO</b>	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
<b>FORQUILHA</b>	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
<b>AMORTECEDORES</b>	n/a
COMPONENTES	
<b>GUIADOR</b>	Giant Connect TR Riser 31.8x690-750mm
<b>PUNHOS</b>	Giant Sole-O Grip
<b>AVANÇO</b>	Giant Contact
<b>ESPIGÃO DE SELIM</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SELIM</b>	Liv Ergo Trail ESG
<b>PEDAIS</b>	Anti-slip Platform
TRANSMISSÃO	
<b>MANETES</b>	Shimano Cues
<b>DESVIADOR TRASEIRO</b>	Shimano Cues 9-speed
<b>TRAVÕES</b>	Shimano MT200, hydraulic disc, 180mm [F/R]
<b>MANÍPULOS DOS TRAVÕES</b>	Shimano MT-200
<b>CASSETTE</b>	Shimano Cues, 11-41T, 9-speed
<b>CORRENTE</b>	KMC eGlide NP/BK, e-bike optimized
<b>CONJUNTO PEDALEIRO</b>	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms, (XS-S: 160mm, M-L: 165mm)
<b>MOVIMENTO CENTRAL</b>	-

RODAS	
<b>AROS</b>	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
<b>CUBOS</b>	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>RAIOS</b>	Stainless steel
<b>PNEUS</b>	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACESSÓRIOS	
<b>LUZES</b>	-
<b>PORTA-BICICLETAS</b>	-

Preço: 2 299,00 €

## GEOMETRIA

QUADRO	XS	S	M
Comprimento do tubo do assento (mm)	365	405	445
Seat Post Insertion Depth (mm)	170	200	240
Ângulo do tubo do assento	78,0°	78,0°	74,0°
Comprimento do tubo superior (mm)	560	570	595
Comprimento do tubo principal (mm)	110	115	105
Ângulo do tubo principal	68,0°	68,0°	68,0°
Garfo ancinho (mm)	44	44	46
Trilha (mm)	106	106	104,5
distância entre eixos (mm)	1151	1162	1139
Comprimento Chain Stay (mm)	450	450	470
Suporte inferior (mm)	45	45	60
Pilha (mm)	596	600	618
Alcançar (mm)	433	442	417
Altura do standover (mm)	717	732	750
Largura do guidão (mm)	690	750	750
Comprimento da haste (mm)	50	50	50
Comprimento da Manivela (mm)	165	165	165
Tamanho da roda	27.5+	27.5+	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.