

# TEMPT E+



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
<b>SENSOR</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
<b>DISPLAY</b>	Giant RideControl Dash 2, high-angle visibility, full color LCD display
<b>BATTERY</b>	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CADRU	
<b>MARIMI</b>	XS, S, M, L (XS-S: 27.5, M-L: 29er)
<b>CULORI</b>	Lunar Eclipse, Seafoam Green
<b>CADRU</b>	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
<b>FURCA</b>	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
<b>SOC</b>	n/a
COMPONENTE	
<b>GHIDON</b>	Giant Connect TR Riser 31.8x690-750mm
<b>GRIPS</b>	Giant Sole-O Grip
<b>PIPA</b>	Giant Contact
<b>TIJA SA</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SA</b>	Liv Ergo Trail ESG
<b>PEDALE</b>	Anti-slip Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
<b>MANETE SCHIMBATOR</b>	Shimano Cues
<b>SCHIMBATOR SPATE</b>	Shimano Cues 9-speed
<b>FRANE</b>	Shimano MT200, hydraulic disc, 180mm [F/R]
<b>MANETE FRANA</b>	Shimano MT-200
<b>PINIOANE</b>	Shimano Cues, 11-41T, 9-speed
<b>LANT</b>	KMC eGlide NP/BK, e-bike optimized
<b>ANGRENAJ</b>	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms, (XS-S: 160mm, M-L: 165mm)
<b>BOTTOM BRACKET</b>	-

ROTI	
<b>JANTE</b>	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
<b>BUTUCI</b>	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>SPITE</b>	Stainless steel
<b>ANVELOPE</b>	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
ACCESSORIES	
<b>LIGHTING</b>	-
<b>CARRIER</b>	-

## GEOMETRIE

CADRU	XS	S	M	L
Seat Tube Length (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Seat Tube Angle	78,0°	78,0°	74,0°	74,0°
Top Tube Length (mm)	560	570	595	615
Head Tube Length (mm)	110	115	105	115
Head Tube Angle	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	44	44	46	46
Trail (mm)	106	106	104,5	104,5
Wheelbase (mm)	1151	1162	1139	1160
Chain Stay Length (mm)	450	450	470	470
Bottom Bracket Drop (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Stand Over Height (mm)	717	732	750	765
Handlebar Width (mm)	690	750	750	750
Stem Length (mm)	50	50	50	60
Crank Length (mm)	165	165	165	
Wheel Size	27.5+	27.5+	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.