



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
OVLÁDAČ	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
OVLÁDACIA JEDNOTKA	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATÉRIA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
NABÍJAČKA	Giant EnergyPak smart charger 4A
KONEKTIVITA	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RÁM	
VELKOSTI	XS, S, M, L (XS-S: 27.5, M-L: 29er)
FARBY	Lunar Eclipse, Seafoam Green
RÁM	ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount
VIDLICA	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
TLMIČ	n/a
KOMPONENTY	
RIADIDLÁ	Giant Connect TR Riser 31.8x690-750mm
GRIPY	Giant Sole-O Grip
PREDSTAVEC	Giant Contact
SEDLOVKA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDADLO	Liv Ergo Trail ESG
PEDÁLE	Anti-slip Platform
POHON	
RADENIE	Shimano Cues
PREHADZOVAČKA	Shimano Cues 9-speed
BRZDY	Shimano MT200, hydraulic disc, 180mm [F/R]
BRZDOVÉ PÁKY	Shimano MT-200
KAZETA	Shimano Cues, 11-41T, 9-speed
REŤAZ	KMC eGlide NP/BK, e-bike optimized
KLUKY	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms, (XS-S: 160mm, M-L: 165mm)
STREDOVÉ ZLOŽENIE	-

KOLESÁ	
RÁFIKY	Liv, GX03V, 27.5 / 29, Alluminium (XS-S: 27.5, M-L: 29)
NÁBOJE	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
ŠPICE	Stainless steel
PNEUMATIKY	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
PRÍSLUŠENSTVO	
OSVETLENIE	-
NOSIČ	-

Cena: 2 699 €

GEOMETRIA

RÁM	XS	S	M	L
Dĺžka sedlovej trubky (mm)	365	405	445	485
Hĺbka vloženia sedlovky (mm)	170	200	240	260
Uhol sedlovej trubky	78,0°	78,0°	74,0°	74,0°
Dĺžka hornej rámovej trubky (mm)	560	570	595	615
Dĺžka hlavovej trubky (mm)	110	115	105	115
Uhol hlavovej trubky	68,0°	68,0°	68,0°	68,0°
Offset vidlice (mm)	44	44	46	46
Trail (mm)	106	106	104,5	104,5
Rázvor (mm)	1151	1162	1139	1160
Dĺžka zadnej stavby (mm)	450	450	470	470
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	45	45	60	60
Stack - výška riadenia (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Výška rámu od zeme (mm)	717	732	750	765
Šírka riaditok (mm)	690	750	750	750
Dĺžka predstavca (mm)	50	50	50	60
Dĺžka klúk (mm)	165	165	165	
Rozmer kolies	27.5+	27.5+	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.