



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZOVALNIK	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	XS, S, M, L (XS-S: 27.5, M-L: 29er)
BARVE	Lunar Eclipse, Seafoam Green
OKVIR	ALUXX aluminum, Overdrive 1½ - 1¼" head tube, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x690-750mm
GRIPS	Giant Sole-O Grip
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Liv Ergo Trail ESG
PEDALA	Anti-slip Platform
POGON	
PRESTAVNE ROČICE	Shimano Cues
ZADNJI MENJALNIK	Shimano Cues 9-speed
ZAVORE	Shimano MT200, hydraulic disc, 180mm [F/R]
ZAVORNE ROČICE	Shimano MT-200
VERIŽNIK	Shimano Cues, 11-41T, 9-speed
VERIGA	KMC eGlide NP/BK, e-bike optimized
GONILKE Z VERIŽNIKI	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms, (XS-S: 160mm, M-L: 165mm)
BOTTOM BRACKET	-

OBROČNIKI	
OBROČI	Liv, GX03V, 27.5 / 29, Alluminium (XS-S: 27.5, M-L: 29)
PESTA	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
DODATNA OPREMA	
SVETILA	-
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Kot sedežne cevi	78,0°	78,0°	74,0°	74,0°
Top Tube Length (mm)	560	570	595	615
Višina glave okvirja (mm)	110	115	105	115
Krmilni kot	68,0°	68,0°	68,0°	68,0°
Zamik vpetja osi (mm)	44	44	46	46
Trail (mm)	106	106	104,5	104,5
Medosna razdalja (mm)	1151	1162	1139	1160
Dolžina cevi ob verigi (mm)	450	450	470	470
Bottom Bracket Drop (mm)	45	45	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	596	600	618	627
Doseg (mm)	433	442	417	435
Višina zgornje cevi (mm)	717	732	750	765
Širina krmila (mm)	690	750	750	750
Dolžina opore krmila (mm)	50	50	50	60
Dolžina gonilke (mm)	165	165	165	
Velikost obročnikov	27.5+	27.5+	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.