

TEMPT E+



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Sport 2, 75Nm, PedalPlus 6-sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels, USB-C (10W)
VISA	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERI	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADDARE	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	XS, S, M, L (XS-S: 27.5, M-L: 29er)
FÄRGER	Lunar Eclipse, Seafoam Green
RAM	ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCM ATB DS coil 29" 100mm travel 15x110 AH axle
BAKDÄMPARE	n/a
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x690-750mm
GREPPAR	Giant Sole-O Grip
STAM	Giant Contact
SADELSTOLPE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Liv Ergo Trail ESG
PEDALER	Anti-slip Platform
DRIVLINA	
VÄXLAR	Shimano Cues
BAKVÄXEL	Shimano Cues 9-speed
BROMSAR	Shimano MT200, hydraulic disc, 180mm [F/R]
BROMSSPAKAR	Shimano MT-200
KASSETT	Shimano Cues, 11-41T, 9-speed
KEDJA	KMC eGlide NP/BK, e-bike optimized
VEVPARTI	Forged allumin direct-mount chainring steel 36T, Forged aluminium crank arms, (XS-S: 160mm, M-L: 165mm)
BROMSREGLAGE	-

HJUL	
FÄLGAR	Liv, GX03V, 27.5 / 29, Alluminum (XS-S: 27.5, M-L: 29)
NAV	eTracker boost alloy 6-bolt disc 15x110mm [F] 12x148mm [R]
EKRAR	Stainless steel
DÄCK	Maxxis Rekon Tanwall XS-S: 27.5x2.4" / M-L: 29 x 2.4" Wire Bead 60TPI
TILLBEHÖR	
BELYSNING	-
BÄRARE	-

Price: 33 990,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	365	405	445	485
Seat Post Insertion Depth (mm)	170	200	240	260
Vinkel sadelrör	78,0°	78,0°	74,0°	74,0°
Topprörets längd (mm)	560	570	595	615
Styrhuvud Längd (mm)	110	115	105	115
Vinkel styrhuvud	68,0°	68,0°	68,0°	68,0°
Gaffelvinkel (mm)	44	44	46	46
Spår (mm)	106	106	104,5	104,5
Hjulbas (mm)	1151	1162	1139	1160
Kedjestagslängd (mm)	450	450	470	470
Nedre fäste Drop (mm)	45	45	60	60
Stack (mm)	596	600	618	627
Reach (mm)	433	442	417	435
Stå över höjden (mm)	717	732	750	765
Styrets bredd (mm)	690	750	750	750
Stamlängd (mm)	50	50	50	60
Vevlängd (mm)	165	165	165	
Hjulstorlek	27.5+	27.5+	29"	29"

All specifications listed are subject to change without notice.