



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Steampunk
<b>FRAME</b>	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Sport, flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
<b>GRIPS</b>	Liv ErgoContact
<b>STEM</b>	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
<b>SEATPOST</b>	Giant D-Fuse, alloy, XS: 300mm, S: 300mm, M: 300mm, L: 350mm
<b>SADDLE</b>	Liv ErgoMax
<b>PEDALS</b>	platform pedal [GT, GU, GV, GC]
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Cues U6000 1x11
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Cues U6020
<b>BRAKES</b>	Tektro HD-R280, hydraulic [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Tektro hydraulic
<b>CASSETTE</b>	Shimano CSLG40011, 11x45
<b>CHAIN</b>	KMC X11 with Missing Link
<b>CRANKSET</b>	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	BB-4000

WHEELS	
<b>RIMS</b>	Giant S-X2 wheelset
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	stainless
<b>TIRES</b>	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
<b>EXTRAS</b>	tubeless prepared, 42mm or 40c max tire size, and rack, kickstand, and fender frame mounts
LIMITS	
<b>MAX TIRE CLEARANCE</b>	42mm

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	350	400	450	500
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°
Top Tube Length (mm)	525	540	560	580
Head Tube Length (mm)	110	135	165	195
Head Tube Angle	70,5°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72,8	69,5	66,2	66,2
Wheelbase (mm)	1014	1020	1031	1046
Chain Stay Length (mm)	425	425	425	425
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	534	560	590	618
Reach (mm)	376	380	385	391
Stand Over Height (mm)	680	710	745	770
Handlebar Width (mm)	600	600	640	640
Stem Length (mm)	80	80	90	100
Crank Length (mm)	165	165	170	172,5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.