



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Steampunk
RAMME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Sport, flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
GRIPS	Liv ErgoContact
STYRSTEM	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
SETEPINNE	Giant D-Fuse, alloy, XS: 300mm, S: 300mm, M: 300mm, L: 350mm
SADEL	Liv ErgoMax
PEDALER	platform pedal [GT, GU, GV, GC]
DRIVVERK	
GIRHENDLER	Shimano Cues U6000 1x11
FRONTGIR	N/A
BAKGIR	Shimano Cues U6020
BREMSE	Tektro HD-R280, hydraulic [F]160mm, [R]160mm
BREMSEHENDLER	Tektro hydraulic
KASSETT	Shimano CSLG40011, 11x45
KJEDE	KMC X11 with Missing Link
KRANK	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	BB-4000

HJUL	
FELG	Giant S-X2 wheelset
NAV	Giant alloy, 12mm thru-axle
EIKE	stainless
DEKK	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
EXTRAS	tubeless prepared, 42mm or 40c max tire size, and rack, kickstand, and fender frame mounts
LIMITS	
MAX TIRE CLEARANCE	42mm

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	350	400	450	500
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°
Top Tube Length (mm)	525	540	560	580
Head Tube Length (mm)	110	135	165	195
Head Tube Angle	70,5°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72,8	69,5	66,2	66,2
Wheelbase (mm)	1014	1020	1031	1046
Chain Stay Length (mm)	425	425	425	425
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	534	560	590	618
Reach (mm)	376	380	385	391
Stand Over Height (mm)	680	710	745	770
Handlebar Width (mm)	600	600	640	640
Stem Length (mm)	80	80	90	100
Crank Length (mm)	165	165	170	172,5
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.