THRIVE 2



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Snow Drift
RAMME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORGAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
KOMPONENTER	
STYR	Giant Sport flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
GREB / STYRBÅND	Liv ErgoContact D3
FREMPIND	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
SADELPIND	Giant D-Fuse, alloy XS:300mm, S:300mm, M:300mm, L:350mm
SADEL	Liv ErgoMax
GEARGRUPPE	
SKIFTEGREB	Shimano CUES U4000, 1x9
BAGSKIFTER	Shimano CUES U4000
BREMSER	Tektro HD-M3110, hydraulic [F]160mm, [R]160mm
BREMSEGREB	Tektro HD-M3110
KASSETTE	Shimano CSLG30009, 11x41
KÆDE	KMC X11 with Missing Link
KRANKSÆT	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KRANKBOKS	BB-4000

HJUL	
FÆLGE	Giant SX-2 wheelset
NAV	Giant alloy, 12mm thru-axle
EGER	stainless
DÆK	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
EKSTRA	tubeless prepared, rack, kickstand, and fender frame mounts
GRÆNSER	
MAX KLINGE STØRRELSE	42mm or 40c max tire size

Pris: 9.519,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	350	400	450	500
Sadelrørsvinkel	74,5°	74,0°	73,5°	73,0°
Overrørslængde (mm)	525	540	560	580
Kronrørslængde (mm)	110	135	165	195
Kronrøsvinkel	70,5°	71,0°	71,5°	71,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Sti (mm)	72,8	69,5	66,2	66,2
Akselafstand (mm)	1014	1020	1031	1046
Kædestagslængde (mm)	425	425	425	425
Krankboks drop (mm)	70	70	70	70
Stack (mm)	534	560	590	618
Reach (mm)	376	380	385	391
Skridthøjde (mm)	680	710	745	770
Styrbredde (mm)	600	600	640	640
Frempindslængde (mm)	80	80	90	100
Pedalarmslængde (mm)	165	165	170	172,5
Hjulstørrelse	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.