

# THRIVE 2



## SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Cosmos Navy
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Sport, flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
GRIPS	Liv ErgoContact
STEM	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
SEATPOST	Giant D-Fuse, alloy, XS: 300mm, S: 300mm, M: 300mm, L: 350mm
SADDLE	Liv ErgoMax
PEDALS	platform pedal [GT, GU, GV, GC]
DRIVETRAIN	
SHIFTERS	Shimano CUES SL-U4000-9R, 1x9
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES RD-U4000
BRAKES	Tektro HD-R280, hydraulic [F]160mm, [R]160mm
BRAKE LEVERS	Tektro hydraulic
CASSETTE	Shimano CSLG30009, 11x41
CHAIN	KMC X11 with Missing Link
CRANKSET	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	BB-4000

WHEELS	
RIMS	Giant SX-2 wheelset
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
EXTRAS	tubeless prepared, 42mm or 40c max tire size, and rack, kickstand, and fender frame mounts
LIMITS	
MAX TIRE CLEARANCE	42mm

Recommended Retail Price: **\$1,150.00**

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (inch)	13.8	15.7	17.7	19.7
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°
Top Tube Length (inch)	20.7	21.3	22	22.8
Head Tube Length (inch)	4.3	5.3	6.5	7.7
Head Tube Angle	70.5°	71.0°	71.5°	71.5°
Fork Rake (inch)	2	2	2	2
Trail (inch)	2.8	2.7	2.6	2.6
Wheelbase (inch)	39.9	40.2	40.6	41.2
Chain Stay Length (inch)	16.7	16.7	16.7	16.7
Bottom Bracket Drop (inch)	2.8	2.8	2.8	2.8
Stack (inch)	21	22	23.2	24.3
Reach (inch)	14.8	15	15.2	15.4
Stand Over Height (inch)	26.8	28	29.3	30.3
Handlebar Width (inch)	23.6	23.6	25.2	25.2
Stem Length (inch)	3.1	3.1	3.5	3.9
Crank Length (inch)	6.5	6.5	6.7	6.8
Wheel Size	700C	700C	700C	700C

*\*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*