



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Cosmos Navy
FRAME	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Sport, flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
HANDVATTEN	Liv ErgoContact
STUURPEN	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
ZADELLEN	Giant D-Fuse, alloy, XS: 300mm, S: 300mm, M: 300mm, L: 350mm
ZADEL	Liv ErgoMax
PEDALEN	platform pedal [GT, GU, GV, GC]
AFMONTAGE	
SHIFTERS	Shimano CUES SL-U4000-9R, 1x9
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano CUES RD-U4000
REMMEN	Tektro HD-R280, hydraulic [F]160mm, [R]160mm
REMHENDELS	Tektro hydraulic
CASSETTE	Shimano CSLG30009, 11x41
AANDRIJVING	KMC X11 with Missing Link
CRANKSET	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	BB-4000

WIELSET	
VELGEN	Giant SX-2 wheelset
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless
BANDEN	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
EXTRA'S	tubeless prepared, 42mm or 40c max tire size, and rack, kickstand, and fender frame mounts
LIMITS	
MAX TIRE CLEARANCE	42mm

Adviesprijs: € 1.199,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	350	400	450	500
Zitbuis hoek	74,5°	74,0°	73,5°	73,0°
Frame Lengte (horizontaal) (mm)	525	540	560	580
Balhoofdbuis Lengte (mm)	110	135	165	195
Balhoofdbuis Hoek	70,5°	71,0°	71,5°	71,5°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	72,8	69,5	66,2	66,2
Wielbasis (mm)	1014	1020	1031	1046
Liggende achtervork lengte (mm)	425	425	425	425
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	534	560	590	618
Reach (mm)	376	380	385	391
Stand Over Height (mm)	680	710	745	770
Stuur breedte (mm)	600	600	640	640
Stuurpen Lengte (mm)	80	80	90	100
Cranklengte (mm)	165	165	170	172,5
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.