THRIVE 2



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Snow Drift
RAM	ALUXX SL-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
KOMPONENTER	
STYRE	Giant Sport flat, 31.8mm, 9-degree backsweep XS: 600mm, S: 600mm, M: 640mm, L: 640mm
GREPPAR	Liv ErgoContact D3
STAM	Giant Contact, 8-degree XS: 80mm, S: 80mm, M: 90mm, L: 100mm
SADELSTOLPE	Giant D-Fuse, alloy XS:300mm, S:300mm, M:300mm, L:350mm
SADEL	Liv ErgoMax
DRIVLINA	
VÄXLAR	Shimano CUES U4000, 1x9
BAKVÄXEL	Shimano CUES U4000
BROMSAR	Tektro HD-M3110, hydraulic [F]160mm, [R]160mm
BROMSSPAKAR	Tektro HD-M3110
KASSETT	Shimano CSLG30009, 11x41
KEDJA	KMC X11 with Missing Link
VEVPARTI	FSA Omega AGX+, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BROMSREGLAGE	BB-4000

HJUL	
FÄLGAR	Giant SX-2 wheelset
NAV	Giant alloy, 12mm thru-axle
EKRAR	stainless
DÄCK	Maxxis Re-Fuse, wirebead, tubeless, 700x40c
EXTRAFUNKTIONER	tubeless prepared, rack, kickstand, and fender frame mounts
GRÄNSER	
MAX KEDJERINGSTORLEK	42mm or 40c max tire size

Price: 14 100,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	350	400	450	500
Vinkel sadelrör	74,5°	74,0°	73,5°	73,0°
Topprörets längd (mm)	525	540	560	580
Styrhuvud Längd (mm)	110	135	165	195
Vinkel styrhuvud	70,5°	71,0°	71,5°	71,5°
Gaffelvinkel (mm)	50	50	50	50
Spår (mm)	72,8	69,5	66,2	66,2
Hjulbas (mm)	1014	1020	1031	1046
Kedjestagslängd (mm)	425	425	425	425
Nedre fäste Drop (mm)	70	70	70	70
Stack (mm)	534	560	590	618
Reach (mm)	376	380	385	391
Stå över höjden (mm)	680	710	745	770
Styrets bredd (mm)	600	600	640	640
Stamlängd (mm)	80	80	90	100
Vevlängd (mm)	165	165	170	172,5
Hjulstorlek	700C	700C	700C	700C

All specifications listed are subject to change without notice.