

THRIVE ADVANCED 0



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, carbon flip chip - dropout, disc
FORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect, flat XS:60cm, S:60cm, M:64cm, L:64cm
GRIPS	Liv ErgoMax
STEM	Giant Contact XS: 80mm, S: 80mm, M: 90mm, L: 100mm
SEATPOST	Giant D-Fuse SL, composite, 350mm
SADDLE	Liv ErgoMax
PEDALS	platform pedal
DRIVETRAIN	
SHIFTERS	SRAM EC AXS, 1x12
FRONT DERAILLEUR	SRAM Rival eTap
REAR DERAILLEUR	SRAM Rival eTap
BRAKES	Shimano BR-U300, hydraulic [F]160mm, [R]160mm
BRAKE LEVERS	Shimano BL-MT201
CASSETTE	SRAM Rival, 10x36
CHAIN	SRAM Rival
CRANKSET	SRAM Rival, 33/46 XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB

WHEELS	
RIMS	Giant P-X2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless
TIRES	Maxxis Receptor, tubeless, 700x40c
EXTRAS	42mm max tire size

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	350	400	450	500				
Seat Tube Angle	74,5° 74,4°	74,0° 73,9°	73,5° 73,4°	73,0° 72,9°				
Top Tube Length (mm)	525	540	560	580				
Head Tube Length (mm)	110	135	165	195				
Head Tube Angle	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	71,5° 71,4°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	72,8 75,3	69,5 71,9	66,2 68,6	66,2 68,6				
Wheelbase (mm)	1013,5 1023,3	1020 1030	1031 1041	1046,3 1056,1				
Chain Stay Length (mm)	425 435	425 435	425 435	425 435				
Bottom Bracket Drop (mm)	70 71	70 71	70 71	70 71				
Stack (mm)	534,1 534,7	559,6 560,2	589,9 590,5	618,4 619				
Reach (mm)	376,9 375,9	379,5 378,5	385,3 384,2	390,9 389,8				
Stand Over Height (mm)	680	710	745	770				
Handlebar Width (mm)	600	600	640	640				
Stem Length (mm)	80	80	90	100				
Crank Length (mm)	165	170	170	172,5				
Wheel Size	700C	700C	700C	700C				

All specifications listed are subject to change without notice.