

THRIVE E+ 1 PRO



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
CONTROLLER	Giant RideControl Ergo
DISPLAY	Giant RideDash EVO
BATTERY	Giant EnergyPak 500, 36V Integrated Lithium-Ion
FRAME	
SIZES	XS, S, M, L
COLORS	Dark Iridescent/Black
FRAME	ALUXX SL-Grade Aluminum
FORK	Advanced-Grade Composite,12x100 thru-axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC Flat , 640mm
STEM	Giant Contact
SEATPOST	Giant D-shape, Composite
SADDLE	Liv Sport Pro
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano SL-RS700, 11-Speed
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano MT201 / BR-U300, hydraulic disc, 160mm
BRAKE LEVERS	Shimano MT201
CASSETTE	Shimano 105, 11-32, 11-Speed
CHAIN	KMC e.11 Turbo, EcoProteq
CRANKSET	Giant custom crankset, 34/50T
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant P-R2 Disc
HUBS	Giant Performance Tracker Road, Sealed Bearing
SPOKES	Sapim E-Lite [r] Race [f]
TIRES	Maxxis Re-Fuse 700x32c Folding Carbon Bead MaxxShield Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart Charger

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	390	430	475	510
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	540	550	560	580
Head Tube Length (mm)	105	110	125	150
Head Tube Angle	71,0°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	68,8	68,8	65,6	65,6
Wheelbase (mm)	1050	1060	1066	1087
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	542	546	562	586
Reach (mm)	385	393	399	412
Stand Over Height (mm)	686	714	749	780
Handlebar Width (mm)	580	580	620	620
Stem Length (mm)	70	80	90	100
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.