

THRIVE E+ 1 PRO



SPECS

HYBRID SYKKEL TEKNOLOGI

MOTOR	Giant SyncDrive Pro
SENSOR	Giant RideControl Ergo
DISPLAY	Giant RideDash EVO
BATTERI	Giant EnergyPak 500, 36V Integrated Lithium-Ion

RAMME

STØRRELSE	XS, S, M, L
FARGE	Dark Iridescent/Black
RAMME	ALUXX SL-Grade Aluminum
GAFFEL	Advanced-Grade Composite, 12x100 thru-axle
DEMPER	N/A

KOMPONENTER

STYRE	Giant Connect XC Flat, 640mm
STYRSTEM	Giant Contact
SETEPINNE	Giant D-shape, Composite
SADEL	Liv Sport Pro
PEDALER	Aluminum Platform

DRIVVERK

GIRHENDLER	Shimano SL-RS700, 11-Speed
FRONTGIR	Shimano 105
BAKGIR	Shimano 105
BREMSER	Shimano MT201 / BR-U300, hydraulic disc, 160mm
BREMSEHENDLER	Shimano MT201
KASSETT	Shimano 105, 11-32, 11-Speed
KJEDE	KMC e.11 Turbo, EcoProteq
KRANK	Giant custom crankset, 34/50T
BOTTOM BRACKET	N/A

HJUL

FELG	Giant P-R2 Disc
NAV	Giant Performance Tracker Road, Sealed Bearing
EIKE	Sapim E-Lite [r] Race [f]
DEKK	Maxxis Re-Fuse 700x32c Folding Carbon Bead MaxxShield Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart Charger

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	390	430	475	510
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	540	550	560	580
Head Tube Length (mm)	105	110	125	150
Head Tube Angle	71,0°	71,0°	71,5°	71,5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	68,8	68,8	65,6	65,6
Wheelbase (mm)	1050	1060	1066	1087
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	542	546	562	586
Reach (mm)	385	393	399	412
Stand Over Height (mm)	686	714	749	780
Handlebar Width (mm)	580	580	620	620
Stem Length (mm)	70	80	90	100
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.