

VIDA E+ LOW -STEP

momentum



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	60Nm torque, 250W Mid Drive Motor, power by YAMAHA, SyncDrive Life motor
CONTROLLER	RideControl One ANT+, 5 power level plus auto mode
DISPLAY	ANT+ Wireless display compatible
BATTERY	500Wh capacity Integrated Panasonic cell, partner with Panasonic, EnergyPak 500
FRAME	
SIZES	LDS: S, M, L
COLOURS	Indigo, Happy Mint
FRAME	ALUXX-Grade aluminium, disc
FORK	ALUXX-Grade aluminium
SHOCK	-
COMPONENTS	
HANDLEBAR	Alloy 50mm rise, 31.8mm
GRIPS	Momentum dual compound
STEM	Alloy, 15 degree
SEATPOST	Giant Alloy, 30.9mm
SADDLE	Selle Royal Essenza Relax
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Nexus 7sp Revoshift
FRONT DERAILLEUR	-
REAR DERAILLEUR	-
BRAKES	Tektro HD-M275, hydraulic disc, 160mm [F/R]
BRAKE LEVERS	Tektro HD-M275
CASSETTE	18T
CHAIN	KMC Z1e
CRANKSET	Alloy, 38T
BOTTOM BRACKET	-

WHEELS	
RIMS	Alloy, Disc
HUBS	Shimano TX505 [F] Nexus 7 [R]
SPOKES	Stainless steel
TYRES	CST Metropolitan Palm Bay, 26x2.35"
EXTRAS	Direct Mount KSA18 Trekking Kickstand
ACCESSORIES	
LIGHTING	-
LOCK	-
CARRIER	-

Price: \$3,999.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	380	430	475
Seat Tube Angle	67.0°	67.0°	67.0°
Top Tube Length (mm)	600	620	640
Head Tube Length (mm)	190	205	210
Head Tube Angle	69.0°	69.0°	69.0°
Fork Rake (mm)	50	50	50
Wheelbase (mm)	1089	1108	1128
Chain Stay Length (mm)	480	480	480
Bottom Bracket Drop (mm)	45	45	45
Stack (mm)	625	639	653
Reach (mm)	335	349	363
Stand Over Height (mm)	473	473	473
Stem Length (mm)	40	40	60
Crank Length (mm)	165	165	165
Wheel Size	26	26	26

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.