



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	25Nm torque, 250W Rear Hub Motor, SyncDrive Move motor
CONTROLLER	RideControl GO, frame integrated LED display, 3 power mode
DISPLAY	ANT+ Wireless display compatible
BATTERY	250Wh capacity Integrated Panasonic cell, partner with Panasonic, EnergyPak 250
FRAME	
SIZES	S, M, L
COLOURS	Asphalt Green, Indigo
FRAME	ALUXX aluminum, 1/2" head tube, 148mm drop-out, integrated KS18 kickstand mount
FORK	ALUXX aluminium, 1/2" steerer
SHOCK	-
COMPONENTS	
HANDLEBAR	Aluminum Dropper 31.8x 400/420mm
GRIPS	Momentum dual compound
STEM	Aluminum 31.8
SEATPOST	Aluminium Forged 2-bolt micro adjust
SADDLE	Selle Royal Vivo Ergo Moderate
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano GRX
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano GRX 11-speed
BRAKES	Shimano GRX
BRAKE LEVERS	Shimano GRX
CASSETTE	Shimano 11-42T, 11-speed
CHAIN	KMC, X10
CRANKSET	Forged Alloy Crank Set, 42T
BOTTOM BRACKET	-

WHEELS	
RIMS	Momentum GX03V 700c Alluminum
HUBS	eTracker Sport, 9mm QR [F], SyncDrive Move Rear Motor [R]
SPOKES	Stainless 13G[r], 14G[f]
TIRES	Kenda Kwick Journey, K1129, 700x38C, K-Shield, w/ Reflective
EXTRAS	-
ACCESSORIES	
LIGHTING	Optional
LOCK	ringlock compatible
CARRIER	Optional front and/or rear

Suggested Retail Price (CDN): \$3,499.00

FRAME GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	460	520	580
Seat Tube Angle	74.5°	73.5°	73.0°
Top Tube Length (mm)	550	575	600
Head Tube Length (mm)	125	150	185
Head Tube Angle	71.0°	72.0°	72.0°
Fork Rake (mm)	45	45	45
Trail (mm)	73.3	66.7	66.7
Wheelbase (mm)	1038	1044	1064
Chain Stay Length (mm)	435	435	435
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	578	605	639
Reach (mm)	390	396	405
Stand Over Height (mm)	730	772	818
Handlebar Width (mm)	600	640	680
Stem Length (mm)	80	90	100
Crank Length (mm)	170	170	170
Wheel Size	700c	700c	700c

All prices and specifications are subject to change without notice.