



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	25Nm torque, 250W Rear Hub Motor, SyncDrive Move motor, Class 1, Max Assist Speed: 20MPH
CONTROLLER	RideControl GO, frame integrated LED display, 3 power mode
DISPLAY	ANT+ Wireless display compatible
BATTERY	250Wh capacity Integrated Panasonic cell, partner with Panasonic, EnergyPak 250
FRAME	
SIZES	XS/S, M, L/XL
COLORS	Color A: Asphalt Green, Color B: Indigo
FRAME	ALUXX aluminum, 1/2" head tube, 148mm drop-out, integrated KS18 kickstand mount
FORK	ALUXX aluminium, 1/2" steerer
SHOCK	-
COMPONENTS	
HANDLEBAR	Aluminum Dropper 31.8x 400/420mm
GRIPS	Momentum dual compound
STEM	Aluminum 31.8
SEATPOST	Aluminium Forged 2-bolt micro adjust
SADDLE	Selle Royal Vivo Ergo Moderate
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano GRX
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano GRX 10-speed
BRAKES	Shimano GRX
BRAKE LEVERS	Shimano GRX
CASSETTE	Shimano 11-36T, 10-speed
CHAIN	KMC, X10
CRANKSET	Forged Alloy Crank Set, 42T
BOTTOM BRACKET	-

WHEELS	
RIMS	Momentum GX03V 700c Alluminum
HUBS	eTracker Sport, 9mm QR [F], SyncDrive Move Rear Motor [R]
SPOKES	Stainless 13G[r], 14G[f]
TIRES	Kenda Kwick Journey, K1129, 700x38C, K-Shield, w/ Reflective
EXTRAS	-
ACCESSORIES	
LIGHTING	Optional
LOCK	ringlock compatible
CARRIER	Optional front and/or rear

Recommended Retail Price: \$2,600.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (inch)	18.1	20.5	22.8
Seat Tube Angle	74.5°	73.5°	73.0°
Top Tube Length (inch)	21.7	22.6	23.6
Head Tube Length (inch)	4.9	5.9	7.3
Head Tube Angle	71.0°	72.0°	72.0°
Fork Rake (inch)	1.8	1.8	1.8
Trail (inch)	2.9	2.6	2.6
Wheelbase (inch)	40.9	41.1	41.9
Chain Stay Length (inch)	17.1	17.1	17.1
Bottom Bracket Drop (inch)	3	3	3
Stack (inch)	22.8	23.8	25.2
Reach (inch)	15.4	15.6	15.9
Stand Over Height (inch)	28.7	30.4	32.2
Handlebar Width (inch)	23.6	25.2	26.8
Stem Length (inch)	3.1	3.5	3.9
Crank Length (inch)	6.7	6.7	6.7
Wheel Size	700c	700c	700c

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*