



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Move motor, 25Nm
CONTROLLER	RideControl GO, frame integrated LED display, 3 power mode
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Compact 250Wh

FRAME

SIZES	S, M, L
COLOURS	Asphalt Green
FRAME	ALUXX-grade aluminium
FORK	ALUXX-grade aluminium
SHOCK	-

COMPONENTS

HANDLEBAR	Aluminium Riser 31.8mm
GRIPS	Momentum dual compound
STEM	Alloy 31.8mm
SEATPOST	Alloy Forged 2-bolt micro adjust
SADDLE	Selle Royal Vivo Ergo Moderate
PEDALS	Platform

DRIVETRAIN

SHIFTERS	Shimano Altus M2010, 9-speed
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Alivio, 9-speed
BRAKES	Tektro HD-R280 hydraulic disc, 160mm rotor
BRAKE LEVERS	Tektro HD-R280
CASSETTE	Shimano HG200, 11-36T, 9-speed
CHAIN	KMC e.9 Sport, e-bike optimized
CRANKSET	Forged Alloy Crank Set, 42T
BOTTOM BRACKET	-

WHEELS

RIMS	Giant alloy disc
HUBS	eTracker Sport, 9mm QR [F] SyncDrive Move Rear Motor [R]
SPOKES	Stainless steel
TIRES	Kenda Kwick Journey, 700x38C
EXTRAS	-

ACCESSORIES

LIGHTING	-
LOCK	-
CARRIER	-

Price: \$3,199.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	460	520	580
Seat Tube Angle	74.5°	73.5°	73.0°
Top Tube Length (mm)	550	575	600
Head Tube Length (mm)	125	150	185
Head Tube Angle	71.0°	72.0°	72.0°
Fork Rake (mm)	45	45	45
Trail (mm)	73.3	66.7	66.7
Wheelbase (mm)	1038	1044	1064
Chain Stay Length (mm)	435	435	435
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	578	605	639
Reach (mm)	390	396	405
Stand Over Height (mm)	730	772	818
Stem Length (mm)	80	90	100
Crank Length (mm)	170	170	170
Wheel Size	700c	700c	700c

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.