



## SPECS

| HYBRID CYCLING TECHNOLOGY |   |
|---------------------------|---|
| <b>MOTOR</b>              | 25Nm torque, 250W Rear Hub Motor, SyncDrive Move motor                          |
| <b>CONTROLLER</b>         | RideControl GO, frame integrated LED display, 3 power mode                      |
| <b>DISPLAY</b>            | ANT+ Wireless display compatible  |
| <b>BATTERY</b>            | 250Wh capacity Integrated Panasonic cell, partner with Panasonic, EnergyPak 250 |
| FRAME                     |   |
| <b>SIZES</b>              | S, M, L   |
| <b>COLOURS</b>            | Asphalt Green, Beeswax  |
| <b>FRAME</b>              | ALUXX aluminum, 1/2" head tube, 148mm drop-out, integrated KS18 kickstand mount |
| <b>FORK</b>               | ALUXX aluminium, 1/2" steerer   |
| <b>SHOCK</b>              | -   |
| COMPONENTS                |   |
| <b>HANDLEBAR</b>          | Aluminum Riser 31.8x 600/640/680mm  |
| <b>GRIPS</b>              | Momentum dual compound  |
| <b>STEM</b>               | Aluminum 31.8   |
| <b>SEATPOST</b>           | Aluminium Forged 2-bolt micro adjust  |
| <b>SADDLE</b>             | Selle Royal Vivo Ergo Moderate  |
| <b>PEDALS</b>             | Aluminum Platform   |
| DRIVETRAIN                |   |
| <b>SHIFTERS</b>           | microSHIFT ADVENT   |
| <b>FRONT DERAILLEUR</b>   | -   |
| <b>REAR DERAILLEUR</b>    | microSHIFT ADVENT 9-speed   |
| <b>BRAKES</b>             | Tektro HD-R280 hydraulic disc, 160mm rotor                                      |
| <b>BRAKE LEVERS</b>       | Tektro HD-R280  |
| <b>CASSETTE</b>           | microSHIFT 11-42T, 9-speed  |
| <b>CHAIN</b>              | KMC e.9 Sport, e-bike optimized   |
| <b>CRANKSET</b>           | Forged Alloy Crank Set, 42T   |
| <b>BOTTOM BRACKET</b>     | -   |

| WHEELS          |  |
|-----------------|--|
| <b>RIMS</b>     | Momentum GX03V 700c Alluminum                                |
| <b>HUBS</b>     | eTracker Sport, 9mm QR [F], SyncDrive Move Rear Motor [R]    |
| <b>SPOKES</b>   | Stainless 13G[r], 14G[f]                                     |
| <b>TIRES</b>    | Kenda Kwick Journey, K1129, 700x38C, K-Shield, w/ Reflective |
| <b>EXTRAS</b>   | -  |
| ACCESSORIES     |  |
| <b>LIGHTING</b> | Optional   |
| <b>LOCK</b>     | ringlock compatible  |
| <b>CARRIER</b>  | Optional front and/or rear                                   |

**Suggested Retail Price (CDN): \$2,999.00**

## FRAME GEOMETRY

| FRAME                    | S     | M     | L     |
|--------------------------|-------|-------|-------|
| Seat Tube Length (mm)    | 460   | 520   | 580   |
| Seat Tube Angle          | 74.5° | 73.5° | 73.0° |
| Top Tube Length (mm)     | 550   | 575   | 600   |
| Head Tube Length (mm)    | 125   | 150   | 185   |
| Head Tube Angle          | 71.0° | 72.0° | 72.0° |
| Fork Rake (mm)           | 45    | 45    | 45    |
| Trail (mm)               | 73.3  | 66.7  | 66.7  |
| Wheelbase (mm)           | 1038  | 1044  | 1064  |
| Chain Stay Length (mm)   | 435   | 435   | 435   |
| Bottom Bracket Drop (mm) | 75    | 75    | 75    |
| Stack (mm)               | 578   | 605   | 639   |
| Reach (mm)               | 390   | 396   | 405   |
| Stand Over Height (mm)   | 730   | 772   | 818   |
| Handlebar Width (mm)     | 600   | 640   | 680   |
| Stem Length (mm)         | 80    | 90    | 100   |
| Crank Length (mm)        | 170   | 170   | 170   |
| Wheel Size               | 700c  | 700c  | 700c  |

*All prices and specifications are subject to change without notice.*